powermaster

DSW

Vehicular Swing Gate Operator

Our Commercial Swing Gate Operator with DC motor controls vehicular gates for high traffic and residential applications. It is ideal for custom homes, apartments, self storage and other commercial properties.

Standard Features:

- Battery Backup
- Soft Start / Soft Stop
- Attractive Low Profile
- Easy Set Limits
- AC Power Outlets
- Plug-in Loop Detectors (optional)
- Easy-Install Design

www.VEpower.net

facebook.com/PowerMasterOperators

SERVICING THE INDUSTRY SINCE 1969

This and other PowerMaster products are proudly distributed by:

DSW

Specifications & Features

- 24VDC direct drive motor offers higher efficiency
- Built-in battery backup - Batteries included (up to 300 cycles with fully charged batteries during power outages)
- Soft-Start/Soft Stop feature for smooth operation
- Optional plug-in loop detectors save time and wiring
- Built-in 3-Button control for simple installation setup
- Power fail operation can be set to open gate or cycle gate
- Maglock or Solenoid lock output
- Solid state circuitry is protected by a plastic enclosure
- Two convenient power outlets for accessories
- Solar and low voltage charging inputs for added power control
- Built-in Radio receiver

COVER: UV PROTECTED POLYETHYLENE
GEARBOX: HEAVY DUTY
MOTOR: 1/2 HP, 24VDC
POWER INPUT: 120 VAC
TRAVEL SPEED: 90 DEGREES IN 15 SECONDS (APPROX.)
ARM ATTACHMENT HEIGHT: 17" FROM OPERATOR BASE
DIMENSIONS: 18" HIGH, 18.5" WIDE, 23.5" DEEPGATE
CAPACITY: 2000 LBS, 18 FEET COMMERCIAL CAPACITY

**** SHIPPING WEIGHT: 160 LBS***

CAUTION!

A moving gate can cause serious injury or death!

Carefully read and follow all safety instructions, precautions, and guidelines when installing and using this product.

Motorized gates are for vehicles only. Pedestrians must use a separate entrance. NO ONE SHOULD CROSS THE PATH OF A MOVING GATE!

Proper reversing devices must be installed on gates to avoid all hazards, pinch points and entrapment. Eliminate all hazards, pinch points and entrapment areas.

Warning signs must be permanenly installed and visible to traffic and pedestrians.

Do not mount operating devices accessible through gates or between a gate and wall.

Never allow children to lay in the path of a gate. Never allow children to operate or play with the gate controls.

Follow UL 325 and ASTMF220-02 standards.

Do not install this product unless all hazards, pinch points and entrapment points are protected.

PowerMaster

www.vepower.net

Proudly Assembled in the U.S.A.